

## High Performance Gas Analysis with Continuous-Wave Cavity Ring-Down Spectroscopy (CW-CRDS) on a New Generation Low-Cost Platform


Yu Chen and Erika Coyne

Tiger Optics LLC, 250 Titus Avenue, Warrington, PA 18976, USA


### How the Spark™ Opens New Vistas

- Field proven, CW-CRDS has found growing acceptance with 1,000s of measurement points worldwide, including metrology institutes, where it is trusted for its accuracy and stability
- Spark™, a new generation platform, brings powerful CW-CRDS technology to customers at a more affordable price
- Joint validation tests with Air Products demonstrate key performance attributes of the Spark: accuracy, linearity, repeatability, speed of response, and low detection limit
- Ideal for numerous industrial process applications, ranging from cylinder filling, to air separation, to lab, and more


### Repeatability




### CRDS Technology = Practical Solution




### Speed of Response



### Baseline



### Experimental Setup for Joint Validation Test



### How the Spark™ Stacks Up

- A rare combination of low cost of ownership and state-of-the-art performance, as validated by joint tests with APCI
- Self-zero & auto-verification throughout full range of moisture excursion: no need to interrupt measurement to tune for baseline
- Small cell volume allows swift tracking of moisture changes and rapid measurement throughput
- Huge dynamic range with the following LDL/UDL specs for moisture in various matrices:

Gas Matrix	N2	O2	Ar	He	H2	Air:CDA
LDL (ppb)	15	7	6	4	10	14
UDL (ppm)	2000	1100	900	450	1750	1800