

**PRODUCT DATASHEET**

# ALOHA+ H<sub>2</sub>O™

Gas Analyzer for Trace Moisture  
in Ammonia



**Designed for trace level moisture analysis in ammonia, the ALOHA+ H<sub>2</sub>O offers:**

- 3 parts-per-billion (ppb) detection capability in ammonia (NH<sub>3</sub>) and sub-ppb in inert matrices
- Rapid response time
- Wide dynamic range
- Absolute and calibration-free measurement technology
- Extremely low cost of ownership
- User-friendly touchscreen and remote communication

# The superior analytical solution for your High-Brightness LED needs

The ALOHA+ H<sub>2</sub>O™ advances moisture detection in ammonia (NH<sub>3</sub>) to unprecedented levels. The analyzer provides specialty gas and High-Brightness LED makers with the exceptional detection limits, accuracy, reliability, speed of response and ease of operation that our customers have come to expect. LED manufacturers rely on our proven Cavity Ring-Down Spectroscopy-based moisture sensors to ensure the ammonia process gas is of the high quality necessary to produce High Brightness LEDs. The cost effective analyzer is quick to install, easy to use and effortless to maintain. There are no off-line periodic sensor maintenance procedures, no span calibrations, no purifier replacement and no pump rebuilds required. The ALOHA+ H<sub>2</sub>O analyzer is fully self-calibrating and the “bright” choice for your detection needs!

## Specifications

### Performance

<b>Operating range:</b>	See table below
<b>Detection limit (LDL, 3<math>\sigma</math>/24h):</b>	See table below
<b>Precision (1<math>\sigma</math>, greater of):</b>	± 1% or 1/3 of LDL
<b>Accuracy (greater of):</b>	± 4% or LDL
<b>Speed of response:</b>	< 5 minutes to 95%
<b>Environmental conditions:</b>	10°C to 40°C, 30% to 80% RH (non-condensing)
<b>Storage temperature:</b>	-10°C to 50°C

---

### Gas Handling System and Conditions\*

<b>Wetted materials:</b>	316L stainless steel, 10 Ra surface finish
<b>Gas connections:</b>	1/4" male VCR inlet and outlet
<b>Leak tested to:</b>	1 x 10 <sup>-9</sup> mbar l / sec
<b>Inlet pressure:</b>	10 - 125 psig (1.7 - 9.6 bara)
<b>Outlet pressure:</b>	<2 Torr (2.7 mbar)
<b>Flow rate:</b>	up to 1.8 slpm (gas dependent)
<b>Sample gases:</b>	Ammonia (NH <sub>3</sub> ) & inert matrices
<b>Gas temperature:</b>	Up to 60°C

---

### Dimensions & Weight

<b>Standard sensor</b> (incl. shutoff valves):	H x W x D: 8.73 x 8.57 x 26.4 in (222 x 218 x 670)
<b>Sensor rack</b> (fits up to two sensors):	H x W x D: 8.73 x 19.0 x 26.4 in (222 x 483 x 670)
<b>Standard sensor weight:</b>	34 lbs (15.4 kg)

---

### Electrical and Interfaces

<b>Platform:</b>	Max Series analyzer
<b>Alarm indicators:</b>	2 user programmable 1 system fault Form C relays
<b>Power requirements:</b>	90 – 240 VAC, 50/60 Hz
<b>Power consumption:</b>	40 Watts max. (excluding vacuum pump)
<b>Signal output:</b>	Isolated 4–20 mA
<b>User interfaces:</b>	5.7" LCD touchscreen. 10/100 Base-T Ethernet. USB, RS-232, RS-485
<b>Data storage:</b>	Internal or external flash drive
<b>Certification:</b>	CE Mark

---

### Performance, CH<sub>4</sub>

	<b>Range</b>	<b>LDL (3<math>\sigma</math>)</b>	<b>Precision (1<math>\sigma</math>) @ zero</b>
<b>In Ammonia:</b>	0 – 20 ppm	3 ppb	1 ppb
<b>In Nitrogen:</b>	0 – 6 ppm	0.5 ppb	0.2 ppb
<b>In Helium:</b>	0 – 3 ppm	0.3 ppb	0.1 ppb
<b>In Argon:</b>	0 – 4 ppm	0.4 ppb	0.15 ppb
<b>In Hydrogen<sup>†</sup>:</b>	0 – 6 ppm	0.5 ppb	0.2 ppb

\*Vacuum source required

<sup>†</sup>Please ensure that the vacuum source used meets all safety requirements for use in pure hydrogen. U.S. Patent # 7,277,177

## GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

---

## CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

### Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

### Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

### Process Insights – APAC


Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

---

For a complete range of products, applications, systems, and service options, please contact us at: [info@process-insights.com](mailto:info@process-insights.com)

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

**EVERYWHERE**