

PRODUCT DATASHEET

SERIES 2520™

Percent Oxygen Analyzer



Product shown with optional flow meter



FEATURES	BENEFITS
State-of-the-Art Sensor Technology	High precision measurements
Light Weight/Compact Design	Easy to carry and transport
Rapid Speed of Response	Senses oxygen changes in seconds
Built-in NICAD Batteries	Provides hours of continuous operation
Uses Standard NICAD's	Replacement batteries found world-wide
Minimum Maintenance	Low cost of ownership
Factory Calibration	Factory calibration and certificate included at no additional charge

System Description

The Series 2520™ Portable Percent Oxygen Analyzer is a light-weight, easy-to-use analyzer that provides accurate and repeatable percent oxygen measurements in a variety of gases. The rugged and compact design of the Series 2520 makes it ideal for industrial applications where spot oxygen measurements need to be made.

The Series 2520 can be configured with one of several measuring ranges from 0-2% to 0-100% oxygen. The standard Series 2520 Portable Percent Oxygen Analyzer is equipped with a 3-1/2 digit liquid crystal display, built-in NICAD batteries, and a universal AC adapter that provides the ability to recharge the NICAD batteries even while powering the analyzer from the adapter.

The Series 2520 Portable Percent Oxygen Analyzer features an extended life oxygen sensor with EES (Enhanced Electrolyte System) that provides exceptional measurement accuracy and stability. For applications where carbon dioxide is present in the sample gas, the EES retards passivation of the sensor anode by allowing the products of oxidation to dissolve in the electrolyte. In effect, the sensor is renewed continuously, resulting in an increase in sensor life. The output from the sensor is temperature compensated.

Depending on the application, the Series 2520 can be equipped with a number of options including; sample filters, sample pumps, pressure regulators, and flow meters, etc.

SPECIFICATIONS

Performance

Measurement Ranges

(Percent Oxygen):	0-2
(Percent Oxygen)	0-5
	0-10
	0-20
	0-25
	0-50
	0-100

Accuracy: ±1% of full scale (± 5% of full scale on ranges ≤ 0-5%)

Linearity: ±1% of full scale

Response Time: 90% of full scale in <20 seconds

Sensor Type: Electrochemical

Temperature Compensation: Standard

Operating Temperature Range: 40° to 104° F (5° to 40°C)

Warranty: 2 years electronics/1 year sensor

Electrical

Display:	3-1/2 digit liquid crystal display
Power Source:	Rechargeable NICAD batteries with universal (90-240 VAC) AC adapter
Analog Output:	Not available

Sample Gas Characteristics

Sample Flow Rate:	1.0 to 2.0 SCFH (0.5 to 1.0 liter/min)
Sample Gas Temperature:	40° to 104°F (5° to 40°C)
Sample Gas Pressure:	0.1 to 1.5 psig (0.007 to 0.1 kg/cm ²)

Construction

Enclosure:	Polycarbonate-rated NEMA 1
Dimensions*:	5.8 in. (147.3 mm) Height 6.7 in. (170.2 mm) Width 3.4 in. (86.4 mm) Depth
Gas Connections:	Quick connect
Weight:	<2 pounds (<0.907 kg)

* Note: All dimensions are without optional equipment

GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910


Process Insights – APAC

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

For a complete range of products, applications, systems, and service options, please contact us at: info@process-insights.com

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

EVERYWHERE