

OXYGEN ANALYZERS



**FEATURES BENEFITS** State-of-the-Art Sensor Technology High precision measurements Light Weight/Compact Design Easy to carry and transport Rapid Speed of Response Senses oxygen changes in seconds **Built-in NICAD Batteries** Provides hours of continuous operation Replacement batteries found world-wide Uses Standard NICAD's Minimum Maintenance Low cost of ownership **Factory Calibration** Factory calibration and certificate included at no additional charge

## **Product Description**

The Series 3520<sup>™</sup> Trace Oxygen Analyzer is a portable, battery operated trace oxygen analyzer designed for industrial and commercial applications where accurate and reliable spot trace oxygen measurements are needed. The Series 3520 Portable Oxygen Analyzer features our long life ambient temperature electrochemical sensor. The enclosure is made from durable polycarbonate and is rated NEMA 1 for general purpose service. The instrument is powered from rechargeable NICAD batteries that are mounted internal to the analyzer. Recharging of the batteries is accomplished using a built-in battery charger with a universal AC adapter. Single measurement ranges are available from 0-10 PPM to 0-20,000 PPM with values displayed on a front panel liquid crystal display (LCD). Options include pressure regulators, flow meters, in-line filters, sample pumps, and block & bleed by-pass sampling systems.

#### High Performance Trace Oxygen Sensor

The Series 3520 Trace Oxygen Analyzer features our long-life ambient temperature electrochemical sensor that has a functional life of up to three times that of most "fuel cell" type sensors. The enhanced mechanical design of the sensor ensures longer life, and virtually eliminates leakage of caustic electrolyte, a nagging (and expensive) problem associated with sensors that require periodic electrolyte maintenance. And, because the sensor is sealed, it is not position sensitive. In addition, unlike ome electrochemical sensors, the readings from the Series 3520 do not require manual adjustment based on changes in the molecular weights of the sample gas i.e. helium, hydrogen, etc. a major advantage for continuous measuring applications. The output from the sensor is both linear and temperature compensated to provide optimum performance.

#### Now Featured a CO<sub>2</sub> Resistant Sensor

A nemesis for many conventional "fuel cell" type trace oxygen sensors are their inability to measure oxygen in gases containing carbon dioxide. Carbon dioxide reacts with potassium hydroxide electrolyte to form carbonic acid and in short time destroys the sensor. Not anymore. We offer an optional  $CO_2$  tolerant trace oxygen sensor with proprietary electrolyte. The  $CO_2$  tolerant sensor is capable of providing accurate oxygen readings in gases containing up to 100%  $CO_2$  without shortening the life of the sensor.

### **SPECIFICATIONS**

#### Performance

Measurement Ranges	
(parts per million):	0-10, 0-50, 0-100, 0-200, 0-500, 0-1,000, 0-5,000, 0-10,000, and 0-20,000
Accuracy <sup>1</sup> :	±1% of full scale
Linearity:	±1% of full scale
Response Time:	90% of full scale response in <10 seconds (typical). The response time for ranges of 0-50 PPM or less depend to a great extent on the design of the sample delivery system including the materials used.

Sensor Type:	Long-life Ambient Temperature Electro-chemical Sensor (Optional CO <sub>2</sub> Resistant Sensor Available)	
Temperature Compensation:	Standard	
<b>Operating Temperature:</b>	: 40° to 104° F (5° to 40°C)	
Warranty:	2 years electronics/1 year sensor	

# **Electrical**

Display:	3-1/2 digit liquid crystal display, (4-1/2 digit for the 0-5,000, 0-10,000, and 0-20,000 ppm range instruments)
Series 3510 Trace Oxygen Transmitter:	Input power 115 or 230 VAC, 50-60 Hz, or 24 VDC
Input Power:	Powered from eight AA Rechargeable NICAD batteries with built-in universal AC battery charger
Analog Output:	No analog output

# Sample Gas Characteristics

Sample Flow Rate:	1.0 to 2.0 SCFH (0.5 to 1.0 liter/min)
Sample Gas Temperature:	40° to 104°F (5° to 40°C)
Sample Gas Pressure Limits:	0.1 to 1.5 psig (0.007 to 0.1 kg/cm²)
Entrained Solids:	<3 mg/ft <sup>3</sup> : no in-line filter required >3 mg/ft <sup>3</sup> : in-line filter is required
Hydrocarbon Mist:	<0.7 mg/ft <sup>3</sup> : no in-line filter required >0.7 mg/ft <sup>3</sup> : in-line filter is required

# Construction

Electronics	Polycarbonate rated NEMA 1
Dimensions*:	6.5 inches (165.1 mm) height 6.5 inches (165.1 mm) width 7.8 inches (196.9 mm) height
Gas Connections:	1/4" stainless steel compression fittings

<sup>1</sup> Stated at constant temperature and constant pressure.

\* Note: All dimensions are without optional equipment



### GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe. Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

### CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

### **Process Insights – The Americas**

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

### **Process Insights – EMEA**

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

### **Process Insights – APAC**

Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

For a complete range of products, applications, systems, and service options, please contact us at: info@process-insights.com

For a complete list of sales & manufacturing sites, please visit: https://www.process-insights.com/about-us/locations/

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



www.process-insights.com Copyright © 2023 Process Insights, Inc. All Rights Reserved.